NPOWER
Power and automation technologies.

DEUTZ®

Series Diesel Generator Sets

40 kVA - 72 kVA

ENGINE

- G-Drive Series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged / turbocharged & air to air charge cooled
- Direct injection
- Mechanic / electronic governor system
- 12 / 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extention pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine jacket water heater (In automatic models)
- Maintenance and operating instructions

ALTERNATOR

- Brushless, single bearing
- H Class insulation type
- IP21-23 Protection class
- Self exciter
- Automatic voltage regulator
- 2/3 Pitch factor windings
- 4 Poles

AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

QUALITY STANDARD DIRECTIVES

- 2006/42/EC (Machinery Directive)
- 2014/30/EC (EMC Directive)
- 2014/35/EC (Low Voltage Directive)
- 2000/14/EC (Noise Emition Directive)

CANOPY / CONTAINER

- Modular type sound-proof canopy / container
- Easy installation type without welding canopy
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Locakable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start / stop failure

OPTIONAL EQUIPMENTS

- Charge ampmeter
- Circuit breakers (In automatic models)
- Residental / Critical type silencer
- Sound-proof canopy or container
- Mobile trailer and truck installation
- Synchronization panel for 2-32 gensets
- 3 pole / 4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Anticondensation heater
- Fuel automation systems
- Different IP and Insulation class alternator
- PMG

INTERNATIONAL QUALITY STANDARD

- EN12601, EN60204, EN12100, EN61000, EN55011
- TS ISO 8528, TS ISO 3744, TS ISO 3746, TS ISO 13857
- EN60034, EN55014, ISO 3046, BS5000, IEC 60034
- VDE 0530, BSE 4999, EN60335, IBC 2015:EC8 2004

Easy maintenance canopy design

Refilling from the outside of the canopy

Canopy made of galvanized steel

Warning system for decreasing fuel with electronic fuel level sender

NPOWER
Power and automation technologies.

DEUTZ®

Series Diesel Generator Sets

	MODEL			N DZ XX 0040	N DZ XX 0060	N DZ XX 0072
GROUP	GEN-SET POWER	STAND BY	kVA	40	60	72
			kW	32	48	58
		PRIME	kVA	36	55	65
			kW	29	44	52
	CANOPY DIMENSION (W x L x H) mm			1000 x 2450 x 1610	1000 x 2450 x 1610	1000 x 2880 x 1610
	CANOPY WEIGHT kg			930	1015	1315
	OPEN DIMENSION (W x L x H) mm			1000 x 2050 x 1390	1000 x 2050 x 1520	1000 x 2400 x 1520
	OPEN WEIGHT			735	820	1095
ENGINE	BRAND			DEUTZ	DEUTZ	DEUTZ
	TYPE			D226B-3D	TD226B-3D	WP4D66E200
	POWER	STAND BY	kW	36,5	55,2	86
		PRIME	kW	32	50,2	78
	SPEED (rpm)			1500	1500	1500
	CYCLE			4	4	4
	DISPLACEMENT (lt)			3,12	3,12	4,5
	NUMBER OF CYLNDERS			3 IN LINE	3 IN LINE	4 IN LINE
	BORE x STROKE (mm x mm)			105 x 120	105 x 120	105 x 130
	COMPRESSION RATIO			16,4:1	15,5:1	18:1
	GOVERNOR TYPE			MECHANIC / ELECTRONIC		
	INDUCTION			NATURAL	TURBOCHARGED	
	COMBUSTION SYSTEM			DIRECT INJECTION		
	COOLING SYSTEM			WATER		
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		7,56	12,35	16,40
		%75 PRIME POWER		5,69	9,26	12,33
		%50 PRIME POWER		3,92	6,54	9,70
	TOTAL LUBRICATION SYSTEM CAPACITY (lt)			7,25	7,25	10
	TOTAL COOLANT CAPACITY (lt)			28	28	15,30
	FUEL TANK CAPACITY (lt)			132	132	180

Npower reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice. All rights reserved.

OHSAS 18001 ISO 9001 ISO 14001

Turkey Discover the potential