

## 715 kVA - 825 kVA

### ENGINE

- G-Drive Series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged / turbocharged & air to air charge cooled
- Direct injection
- Mechanic / electronic governor system
- 12 / 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine jacket water heater (In automatic models)
- Maintenance and operating instructions

### ALTERNATOR

- Brushless, single bearing
- H Class insulation type
- IP21-23 Protection class
- Self exciter
- Automatic voltage regulator
- 2/3 Pitch factor windings
- 4 Poles

### AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

### QUALITY STANDARD DIRECTIVES

- 2006/42/EC (Machinery Directive)
- 2014/30/EC (EMC Directive)
- 2014/35/EC (Low Voltage Directive)
- 2000/14/EC (Noise Emission Directive)

### CANOPY / CONTAINER

- Modular type sound-proof canopy / container
- Easy installation type without welding canopy
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

### PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start / stop failure

### OPTIONAL EQUIPMENTS

- Charge ampmeter
- Circuit breakers (In automatic models)
- Residential / Critical type silencer
- Sound-proof canopy or container
- Mobile trailer and truck installation
- Synchronization panel for 2-32 gensets
- 3 pole / 4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Anticondensation heater
- Fuel automation systems
- Different IP and Insulation class alternator
- PMG

### INTERNATIONAL QUALITY STANDARD

- EN12601, EN60204, EN12100, EN61000, EN55011
- TS ISO 8528, TS ISO 3744, TS ISO 3746, TS ISO 13857
- EN60034, EN55014, ISO 3046, BS5000, IEC 60034
- VDE 0530, BSE 4999, EN60335, IEC 60335-1:2004



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender

MODEL				N DF XX 0715	N DF XX 0825
GROUP	GEN-SET POWER	STAND BY	kVA	715	825
			kW	572	660
		PRIME	kVA	650	750
			kW	520	600
	CANOPY DIMENSION (W x L x H) mm			1700x4200x2715	1700x4200x2715
	CANOPY WEIGHT kg			7098,9	7464
	OPEN DIMENSION (W x L x H) mm			1700x3750x2050	1700x3750x2050
	OPEN WEIGHT			6374,4	6739
ENGINE	BRAND			DONGFENG	DONGFENG
	TYPE			SYG266TAD63	SY283TAD72
	POWER	STAND BY	kW	602	695
		PRIME	kW	547	631
	SPEED (rpm)			1500	1500
	CYCLE			4	4
	DISPLACEMENT (lt)			26,6	29,6
	NUMBER OF CYLNDERS			12 V TYPE	12 V TYPE
	BORE x STROKE (mm x mm)			135 X 155	138 X 165
	COMPRESSION RATIO			16: 1	14,6:1
	GOVERNOR TYPE			ELECTRONIC	
	INDUCTION			TURBOCHARGED - AIR TO AIR COOLED	
	COMBUSTION SYSTEM			DIRECT	
	COOLING SYSTEM			WATER	
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		145,35	166,57
		%75 PRIME POWER		110,47	126,59
		%50 PRIME POWER		73,95	84,66
	TOTAL LUBRICATION SYSTEM CAPACITY (lt)			57,4	62
	TOTAL COOLANT CAPACITY (lt)			110	132
	FUEL TANK CAPACITY (lt)			1272	1272

Npower reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice. All rights reserved.