

330 kVA - 385 kVA

ENGINE

- G-Drive Series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged / turbocharged & air to air charge cooled
- Direct injection
- Mechanic / electronic governor system
- 12 / 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine jacket water heater (In automatic models)
- Maintenance and operating instructions

ALTERNATOR

- Brushless, single bearing
- H Class insulation type
- IP21-23 Protection class
- Self exciter
- Automatic voltage regulator
- 2/3 Pitch factor windings
- 4 Poles

AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

QUALITY STANDARD DIRECTIVES

- 2006/42/EC (Machinery Directive)
- 2014/30/EC (EMC Directive)
- 2014/35/EC (Low Voltage Directive)
- 2000/14/EC (Noise Emission Directive)

CANOPY / CONTAINER

- Modular type sound-proof canopy / container
- Easy installation type without welding canopy
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start / stop failure

OPTIONAL EQUIPMENTS

- Charge ampmeter
- Circuit breakers (In automatic models)
- Residential / Critical type silencer
- Sound-proof canopy or container
- Mobile trailer and truck installation
- Synchronization panel for 2-32 gensets
- 3 pole / 4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Anticondensation heater
- Fuel automation systems
- Different IP and Insulation class alternator
- PMG

INTERNATIONAL QUALITY STANDARD

- EN12601, EN60204, EN12100, EN61000, EN55011
- TS ISO 8528, TS ISO 3744, TS ISO 3746, TS ISO 13857
- EN60034, EN55014, ISO 3046, BS5000, IEC 60034
- VDE 0530, BSE 4999, EN60335, IEC 60335-1:2004



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender

MODEL				N DO XX 0330	N DO XX 0355	N DO XX 0385
GROUP	GEN-SET POWER	STAND BY	kVA	330	355	385
			kW	260	285	310
		PRIME	kVA	300	320	350
			kW	240	256	280
	CANOPY DIMENSION (W x L x H) mm			1200 x 3800 x 1940	1300 x 3950 x 2135	1300 x 3950 x 2135
	CANOPY WEIGHT kg			3140	3500	3600
	OPEN DIMENSION (W x L x H) mm			1100 x 3000 x 1650	1300 x 3200 x 1700	1300 x 3200 x 1700
	OPEN WEIGHT			1750	2505	2580
ENGINE	BRAND			DOOSAN	DOOSAN	DOOSAN
	TYPE			P126TI-II	DP126LA	DP126LB
	POWER	STAND BY	kW	294	342	362
		PRIME	kW	265	307	327
	SPEED (rpm)			1500	1500	1500
	CYCLE			4	4	4
	DISPLACEMENT (lt)			11,051	11,051	11,051
	NUMBER OF CYLNDERS			6 IN LINE	6 IN LINE	6 IN LINE
	BORE x STROKE (mm x mm)			123 x 155	123 x 155	123 x 155
	COMPRESSION RATIO			17,1 : 1	17,2 : 1	17,2 : 1
	GOVERNOR TYPE			ELECTRONIC		
	INDUCTION			TURBOCHARGED	TURBOCHARGED - AIR TO AIR CHARGE COOLED	
	COMBUSTION SYSTEM			DIRECT INJECTION		
	COOLING SYSTEM			WATER		
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		63	68	74
		%75 PRIME POWER		47	51	55
		%50 PRIME POWER		31	34	36
	TOTAL LUBRICATION SYSTEM CAPACITY (lt)			23	44	44
	TOTAL COOLANT CAPACITY (lt)			51	51	51
	FUEL TANK CAPACITY (lt)			290	290	290

Npower reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice. All rights reserved.