NPOWER
Power and automation technologies.

Perkins
Series Diesel Generator Sets

33 kVA - 66 kVA

ENGINE

- G-Drive Series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged / turbocharged & air to air charge cooled
- Direct injection
- Mechanic / electronic governor system
- 12 / 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extention pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine jacket water heater (In automatic models)
- Maintenance and operating instructions

ALTERNATOR

- Brushless, single bearing
- H Class insulation type
- IP21-23 Protection class
- Self exciter
- Automatic voltage regulator
- 2/3 Pitch factor windings
- 4 Poles

AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

QUALITY STANDARD DIRECTIVES

- 2006/42/EC (Machinery Directive)
- 2014/30/EC (EMC Directive)
- 2014/35/EC (Low Voltage Directive)
- 2000/14/EC (Noise Emition Directive)

CANOPY / CONTAINER

- Modular type sound-proof canopy / container
- Easy installation type without welding canopy
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Locakable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start / stop failure

OPTIONAL EQUIPMENTS

- Charge ampmeter
- Circuit breakers (In automatic models)
- Residental / Critical type silencer
- Sound-proof canopy or container
- Mobile trailer and truck installation
- Synchronization panel for 2-32 gensets
- 3 pole / 4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Anticondensation heater
- Fuel automation systems
- Different IP and Insulation class alternator
- PMG

INTERNATIONAL QUALITY STANDARD

- EN12601, EN60204, EN12100, EN61000, EN55011
- TS ISO 8528, TS ISO 3744, TS ISO 3746, TS ISO 13857
- EN60034, EN55014, ISO 3046, BS5000, IEC 60034
- VDE 0530, BSE 4999, EN60335, IBC 2015:EC8 2004


Easy maintenance canopy design


Refilling from the outside of the canopy


Canopy made of galvanized steel


Warning system for decreasing fuel with electronic fuel level sender

NPOWER
Power and automation technologies.

Perkins

Series Diesel Generator Sets

	MODEL			N PR XX 0033	N PR XX 0050	N PR XX 0066
GROUP	GEN-SET POWER	STAND BY	kVA	33	50	66
			kW	26,4	40	52,8
		PRIME	kVA	30	45	60
			kW	24	36	48
	CANOPY DIMENSION (W x L x H) mm			1000 x 2450 x 1610	1000 x 2450 x 1610	1000 x 2450 x 1610
	CANOPY WEIGHT kg			920	970	1085
	OPEN DIMENSION (W x L x H) mm			1000 x 2050 x 1400	1000 x 2050 x 1400	1000 x 2050 x 1400
	OPEN WEIGHT			725	775	890
ENGINE	BRAND			PERKINS	PERKINS	PERKINS
	TYPE			1103A - 33G	1103A - 33TG1	1103A - 33TG2
	POWER	STAND BY	kW	30,4	45,6	59,3
		PRIME	kW	27,7	41,3	53,8
	SPEED (rpm)			1500	1500	1500
	CYCLE			4	4	4
	DISPLACEMENT (lt)			3,3	3,3	3,3
	NUMBER OF CYLNDERS			3 IN LINE	3 IN LINE	3 IN LINE
	BORE x STROKE (mm x mm)			105 x 127	105 x 127	105 x 127
	COMPRESSION RATIO			19,25 : 1	17,25 : 1	17,25 : 1
	GOVERNOR TYPE			MECHANIC	MECHANIC/ ELECTRONIC	
	INDUCTION			NATURAL	TURBOCHARGED	
	COMBUSTION SYSTEM			DIRECT INJECTION		
	COOLING SYSTEM			WATER		
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		7,20	10,80	13,9
		%75 PRIME POWER		5,61	8,23	10,4
		%50 PRIME POWER		4,06	5,83	7,2
	TOTAL LUBRICATION SYSTEM CAPACITY (lt)			8,3	7,9	7,9
	TOTAL COOLANT CAPACITY (lt)			10,2	10,2	10,2
	FUEL TANK CAPACITY (lt)			132	132	132

Npower reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice. All rights reserved.

OHSAS 18001 ISO 9001 ISO 14001

Turkey Discover the potential