

450 kVA - 550 kVA

ENGINE

- G-Drive Series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged / turbocharged & air to air charge cooled
- Direct injection
- Mechanic / electronic governor system
- 12 / 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine jacket water heater (In automatic models)
- Maintenance and operating instructions

ALTERNATOR

- Brushless, single bearing
- H Class insulation type
- IP21-23 Protection class
- Self exciter
- Automatic voltage regulator
- 2/3 Pitch factor windings
- 4 Poles

AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

QUALITY STANDARD DIRECTIVES

- 2006/42/EC (Machinery Directive)
- 2014/30/EC (EMC Directive)
- 2014/35/EC (Low Voltage Directive)
- 2000/14/EC (Noise Emission Directive)

CANOPY / CONTAINER

- Modular type sound-proof canopy / container
- Easy installation type without welding canopy
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start / stop failure

OPTIONAL EQUIPMENTS

- Charge ampmeter
- Circuit breakers (In automatic models)
- Residential / Critical type silencer
- Sound-proof canopy or container
- Mobile trailer and truck installation
- Synchronization panel for 2-32 gensets
- 3 pole / 4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Anticondensation heater
- Fuel automation systems
- Different IP and Insulation class alternator
- PMG

INTERNATIONAL QUALITY STANDARD

- EN12601, EN60204, EN12100, EN61000, EN55011
- TS ISO 8528, TS ISO 3744, TS ISO 3746, TS ISO 13857
- EN60034, EN55014, ISO 3046, BS5000, IEC 60034
- VDE 0530, BSE 4999, EN60335, IEC 60335-1:2004



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender

MODEL				N PR XX 0450	N PR XX 0500	N PR XX 0550
GROUP	GEN-SET POWER	STAND BY	kVA	450	500	550
			kW	360	400	440
		PRIME	kVA	400	455	500
			kW	320	364	400
	CANOPY DIMENSION (W x L x H) mm			1500 x 4400 x 2660	1500 x 4400 x 2660	1500 x 4400 x 2660
	CANOPY WEIGHT kg			3610	3815	3850
	OPEN DIMENSION (W x L x H) mm			1500 x 3600 x 2200	1500 x 3600 x 2200	1500 x 3600 x 2200
	OPEN WEIGHT			3105	3310	3345
ENGINE	BRAND			PERKINS	PERKINS	PERKINS
	TYPE			2206A - E13TAG3	2506A - E15TAG1	2506A - E15TAG2
	POWER	STAND BY	kW	392	435	478
		PRIME	kW	349	396	435
	SPEED (rpm)			1500	1500	1500
	CYCLE			4	4	4
	DISPLACEMENT (lt)			12,5	15,2	15,2
	NUMBER OF CYLNDERS			6 IN LINE	6 IN LINE	6 IN LINE
	BORE x STROKE (mm x mm)			130 x 157	137 x 171	137 x 171
	COMPRESSION RATIO			16,3 : 1	16,0:1	16,0:1
	GOVERNOR TYPE			ELECTRONIC		
	INDUCTION			TURBOCHARGED - AIR TO AIR CHARGE COOLED		
	COMBUSTION SYSTEM			DIRECT INJECTION		
	COOLING SYSTEM			WATER		
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		81,00	95,00	100,00
		%75 PRIME POWER		62,00	72,00	76,00
		%50 PRIME POWER		42,00	50,00	53,00
	TOTAL LUBRICATION SYSTEM CAPACITY (lt)			40	62	62
	TOTAL COOLANT CAPACITY (lt)			51,40	58	58
	FUEL TANK CAPACITY (lt)			970	970	970

Npower reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice. All rights reserved.