

1385 kVA - 1656 kVA

ENGINE

- G-Drive Series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged / turbocharged & air to air charge cooled
- Direct injection
- Mechanic / electronic governor system
- 12 / 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine jacket water heater (In automatic models)
- Maintenance and operating instructions

ALTERNATOR

- Brushless, single bearing
- H Class insulation type
- IP21-23 Protection class
- Self exciter
- Automatic voltage regulator
- 2/3 Pitch factor windings
- 4 Poles

AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

QUALITY STANDARD DIRECTIVES

- 2006/42/EC (Machinery Directive)
- 2014/30/EC (EMC Directive)
- 2014/35/EC (Low Voltage Directive)
- 2000/14/EC (Noise Emission Directive)

CANOPY / CONTAINER

- Modular type sound-proof canopy / container
- Easy installation type without welding canopy
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start / stop failure

OPTIONAL EQUIPMENTS

- Charge ampmeter
- Circuit breakers (In automatic models)
- Residential / Critical type silencer
- Sound-proof canopy or container
- Mobile trailer and truck installation
- Synchronization panel for 2-32 gensets
- 3 pole / 4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Anticondensation heater
- Fuel automation systems
- Different IP and Insulation class alternator
- PMG

INTERNATIONAL QUALITY STANDARD

- EN12601, EN60204, EN12100, EN61000, EN55011
- TS ISO 8528, TS ISO 3744, TS ISO 3746, TS ISO 13857
- EN60034, EN55014, ISO 3046, BS5000, IEC 60034
- VDE 0530, BSE 4999, EN60335, IEC 60335-1:2004



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender

MODEL				N PR XX 1385	N PR XX 1500	N PR XX 1656
GROUP	GEN-SET POWER	STAND BY	kVA	1385	1500	1656
			kW	1108	1200	1325
		PRIME	kVA	1250	1350	1505
			kW	1000	1080	1204
	CANOPY DIMENSION (W x L x H) mm			N/A	N/A	N/A
	CANOPY WEIGHT kg			N/A	N/A	N/A
	OPEN DIMENSION (W x L x H) mm			2200 x 5350 x 2750	2200 x 5350 x 2750	2200 x 5350 x 2750
	OPEN WEIGHT			8080	8745	8745
	CONTAINER DIMENSION (W x L x H) mm			N/A	N/A	N/A
	CONTAINER WEIGHT kg			N/A	N/A	N/A
ENGINE	BRAND			PERKINS	PERKINS	PERKINS
	TYPE			4012 - 46TWG2A	4012 - 46TAG1A	4012 - 46TAG2A
	POWER	STAND BY	kW	1166	1263	1395
		PRIME	kW	1055	1148	1267
	SPEED (rpm)			1500	1500	1500
	CYCLE			4	4	4
	DISPLACEMENT (lt)			45,842	45,842	45,842
	NUMBER OF CYLNDERS			12 - 60° V	12 - 60° V	12 - 60° V
	BORE x STROKE (mm x mm)			160 x 190	160 x 190	160 x 190
	COMPRESSION RATIO			13,6:1	13:1	13,6:1
	GOVERNOR TYPE			ELECTRONIC		
	INDUCTION			TURBOCHARGED - AIR TO WATER CHARGE COOLED	TURBOCHARGED - AIR TO AIR CHARGE COOLED	
	COMBUSTION SYSTEM			DIRECT INJECTION		
	COOLING SYSTEM			WATER		
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		258,00	281,00	301,00
		%75 PRIME POWER		196,00	212,00	237,00
		%50 PRIME POWER		143,00	154,00	162,00
	TOTAL LUBRICATION SYSTEM CAPACITY (lt)			177	177	177
	TOTAL COOLANT CAPACITY (lt)			210	210	210
	FUEL TANK CAPACITY (lt)			2500	2500	2500

Npower reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice. All rights reserved.

