

220 kVA - 290 kVA

ENGINE

- G-Drive Series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged / turbocharged & air to air charge cooled
- Direct injection
- Mechanic / electronic governor system
- 12 / 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine jacket water heater (In automatic models)
- Maintenance and operating instructions

ALTERNATOR

- Brushless, single bearing
- H Class insulation type
- IP21-23 Protection class
- Self exciter
- Automatic voltage regulator
- 2/3 Pitch factor windings
- 4 Poles

AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

QUALITY STANDARD DIRECTIVES

- 2006/42/EC (Machinery Directive)
- 2014/30/EC (EMC Directive)
- 2014/35/EC (Low Voltage Directive)
- 2000/14/EC (Noise Emission Directive)

CANOPY / CONTAINER

- Modular type sound-proof canopy / container
- Easy installation type without welding canopy
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start / stop failure

OPTIONAL EQUIPMENTS

- Charge ampmeter
- Circuit breakers (In automatic models)
- Residential / Critical type silencer
- Sound-proof canopy or container
- Mobile trailer and truck installation
- Synchronization panel for 2-32 gensets
- 3 pole / 4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Anticondensation heater
- Fuel automation systems
- Different IP and Insulation class alternator
- PMG

INTERNATIONAL QUALITY STANDARD

- EN12601, EN60204, EN12100, EN61000, EN55011
- TS ISO 8528, TS ISO 3744, TS ISO 3746, TS ISO 13857
- EN60034, EN55014, ISO 3046, BS5000, IEC 60034
- VDE 0530, BSE 4999, EN60335, IEC 60335-1:2004



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender

MODEL				N SD XX 0220	N SD XX 0265	N SD XX 0290
GROUP	GEN-SET POWER	STAND BY	kVA	220	265	290
			kW	176	212	232
		PRIME	kVA	198	238	261
			kW	158	191	209
	CANOPY DIMENSION (W x L x H) mm			1150 x 2820 x 2400	1150 x 2820 x 2400	1150 x 2820 x 2400
	CANOPY WEIGHT kg			3000	3165	3165
	OPEN DIMENSION (W x L x H) mm			1150 x 3340 x 1960	1150 x 3340 x 1960	1150 x 3340 x 1960
	OPEN WEIGHT			2705	2865	2865
ENGINE	BRAND			SDEC	SDEC	SDEC
	TYPE			SC7H250D2	SC9D310D2	SC9D340D2
	POWER	STAND BY	kW	178	219	246
		PRIME	kW	161	199	219
	SPEED (rpm)			1500	1500	1500
	CYCLE			4	4	4
	DISPLACEMENT (lt)			6,44	8,82	8,82
	NUMBER OF CYLNDERS			6 IN LINE	6 IN LINE	6 IN LINE
	BORE x STROKE (mm x mm)			105 x 124	114 x 144	114 x 144
	COMPRESSION RATIO			16,0 : 1	18:01	16,5 : 1
	GOVERNOR TYPE			ELECTRONIC	ELECTRONIC	ELECTRONIC
	INDUCTION			TURBOCHARGED - AIR TO AIR CHARGE COOLED	TURBOCHARGED - AIR TO AIR CHARGE COOLED	TURBOCHARGED - AIR TO AIR CHARGE COOLED
	COMBUSTION SYSTEM			Direct	Direct	Direct
	COOLING SYSTEM			WATER	WATER	WATER
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		39,3	50,6	54,1
		%75 PRIME POWER		29,1	38,2	40,8
		%50 PRIME POWER		19,4	26,3	27,3
	TOTAL LUBRICATION SYSTEM CAPACITY (lt)			17,5	19	25
	TOTAL COOLANT CAPACITY (lt)			9,6	12	12
	FUEL TANK CAPACITY (lt)					

Npower reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice. All rights reserved.

