

1500 kVA - 1700 kVA

ENGINE

- G-Drive Series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged / turbocharged & air to air charge cooled
- Direct injection
- Mechanic / electronic governor system
- 12 / 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine jacket water heater (In automatic models)
- Maintenance and operating instructions

ALTERNATOR

- Brushless, single bearing
- H Class insulation type
- IP21-23 Protection class
- Self exciter
- Automatic voltage regulator
- 2/3 Pitch factor windings
- 4 Poles

AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

QUALITY STANDARD DIRECTIVES

- 2006/42/EC (Machinery Directive)
- 2014/30/EC (EMC Directive)
- 2014/35/EC (Low Voltage Directive)
- 2000/14/EC (Noise Emission Directive)

CANOPY / CONTAINER

- Modular type sound-proof canopy / container
- Easy installation type without welding canopy
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start / stop failure

OPTIONAL EQUIPMENTS

- Charge ampmeter
- Circuit breakers (In automatic models)
- Residential / Critical type silencer
- Sound-proof canopy or container
- Mobile trailer and truck installation
- Synchronization panel for 2-32 gensets
- 3 pole / 4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Anticondensation heater
- Fuel automation systems
- Different IP and Insulation class alternator
- PMG

INTERNATIONAL QUALITY STANDARD

- EN12601, EN60204, EN12100, EN61000, EN55011
- TS ISO 8528, TS ISO 3744, TS ISO 3746, TS ISO 13857
- EN60034, EN55014, ISO 3046, BS5000, IEC 60034
- VDE 0530, BSE 4999, EN60335, IEC 2015:EC8 2004



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender

MODEL				N BD XX 1500	N BD XX 1650	N BD XX 1700	
GROUP	GEN-SET POWER	STAND BY	kVA	1500	1650	1700	
			kW	1200	1320	1360	
		PRIME	kVA	1364	1500	1545	
			kW	1091	1200	1236	
	CANOPY DIMENSION (W x L x H) mm				N/A	N/A	N/A
	CANOPY WEIGHT kg				N/A	N/A	N/A
	OPEN DIMENSION (W x L x H) mm				N/A	N/A	N/A
	OPEN WEIGHT				N/A	N/A	N/A
ENGINE	BRAND			BAUDOUIIN		BAUDOUIIN	
	TYPE			12M33G1500/5^		12M33G1650/5	
	POWER	STAND BY	kW	1320	1450	1530	
		PRIME	kW	1200	1318 *	1390	
	SPEED (rpm)			1500		1500	
	CYCLE			4		4	
	DISPLACEMENT (lt)			39,2		52,3	
	NUMBER OF CYLNDERS			12 V		16 V	
	BORE x STROKE (mm x mm)			150 x 185		150 x 185	
	COMPRESSION RATIO			15 : 1		15 : 1	
	GOVERNOR TYPE			ELECTRONIC		ECU	
	INDUCTION			TURBOCHARGED - AIR TO AIR COOLED			TURBOCHARGED - AIR TO WATER COOLED
	COMBUSTION SYSTEM			DIRECT			
	COOLING SYSTEM			WATER			
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		N/A	N/A	325,2	
		%75 PRIME POWER		N/A	N/A	241,8	
		%50 PRIME POWER		N/A	N/A	163,7	
TOTAL LUBRICATION SYSTEM CAPACITY (lt)			155	480	171		
TOTAL COOLANT CAPACITY (lt)			303	N/A	542		
FUEL TANK CAPACITY (lt)			N/A	N/A	N/A		

Npower reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice. All rights reserved.

