

825 kVA - 1000 kVA

ENGINE

- G-Drive Series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged / turbocharged & air to air charge cooled
- Direct injection
- Mechanic / electronic governor system
- 12 / 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine jacket water heater (In automatic models)
- Maintenance and operating instructions

ALTERNATOR

- Brushless, single bearing
- H Class insulation type
- IP21-23 Protection class
- Self exciter
- Automatic voltage regulator
- 2/3 Pitch factor windings
- 4 Poles

AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

QUALITY STANDARD DIRECTIVES

- 2006/42/EC (Machinery Directive)
- 2014/30/EC (EMC Directive)
- 2014/35/EC (Low Voltage Directive)
- 2000/14/EC (Noise Emission Directive)

CANOPY / CONTAINER

- Modular type sound-proof canopy / container
- Easy installation type without welding canopy
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start / stop failure

OPTIONAL EQUIPMENTS

- Charge ampmeter
- Circuit breakers (In automatic models)
- Residential / Critical type silencer
- Sound-proof canopy or container
- Mobile trailer and truck installation
- Synchronization panel for 2-32 gensets
- 3 pole / 4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Anticondensation heater
- Fuel automation systems
- Different IP and Insulation class alternator
- PMG

INTERNATIONAL QUALITY STANDARD

- EN12601, EN60204, EN12100, EN61000, EN55011
- TS ISO 8528, TS ISO 3744, TS ISO 3746, TS ISO 13857
- EN60034, EN55014, ISO 3046, BS5000, IEC 60034
- VDE 0530, BSE 4999, EN60335, IEC 60335-1:2004



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender

MODEL				N BD XX 0825	N BD XX 0900	N BD XX 1000
GROUP	GEN-SET POWER	STAND BY	kVA	825	900	1000
			kW	660	720	800
		PRIME	kVA	750	818	900
			kW	600	655	720
	CANOPY DIMENSION (W x L x H) mm			2200 x 5150 x 3425	2200 x 5150 x 3425	2200 x 5150 x 3425
	CANOPY WEIGHT kg			7480	7790	7890
	OPEN DIMENSION (W x L x H) mm			2200 x 4900 x 2580	2200 x 4900 x 2580	2200 x 4900 x 2580
	OPEN WEIGHT			6000	6310	6410
ENGINE	BRAND			BAUDOUIN	BAUDOUIN	BAUDOUIN
	TYPE			6M33G825/5	12M26G900/5e2	12M26G1000/5e2
	POWER	STAND BY	kW	725	792	902
		PRIME	kW	659	720	820
	SPEED (rpm)			1500	1500	1500
	CYCLE			4	4	4
	DISPLACEMENT (lt)			19,6	31,8	31,8
	NUMBER OF CYLINDERS			6 CYLINDERS V-TYPE	12 CYLINDERS V-TYPE	12 CYLINDERS V-TYPE
	BORE x STROKE (mm x mm)			150 X 185	150 X 150	150 X 150
	COMPRESSION RATIO			15,0:1	15,5:1	15,5:1
	GOVERNOR TYPE			ELECTRONIC		
	INDUCTION			TURBOCHARGED - INTERCOOLER		
	COMBUSTION SYSTEM			DIRECT		
	COOLING SYSTEM			WATER		
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		150,1	172,5	196,8
		%75 PRIME POWER		112,2	130,4	147,2
		%50 PRIME POWER		72,5	91	101,8
	TOTAL LUBRICATION SYSTEM CAPACITY (lt)			62	113	113
	TOTAL COOLANT CAPACITY (lt)			129	180	198
	FUEL TANK CAPACITY (lt)			2000	2000	2000

Npower reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice. All rights reserved.

