

385 kVA - 500 kVA

ENGINE

- G-Drive Series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged / turbocharged & air to air charge cooled
- Direct injection
- Mechanic / electronic governor system
- 12 / 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine jacket water heater (In automatic models)
- Maintenance and operating instructions

ALTERNATOR

- Brushless, single bearing
- H Class insulation type
- IP21-23 Protection class
- Self exciter
- Automatic voltage regulator
- 2/3 Pitch factor windings
- 4 Poles

AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

QUALITY STANDARD DIRECTIVES

- 2006/42/EC (Machinery Directive)
- 2014/30/EC (EMC Directive)
- 2014/35/EC (Low Voltage Directive)
- 2000/14/EC (Noise Emission Directive)

CANOPY / CONTAINER

- Modular type sound-proof canopy / container
- Easy installation type without welding canopy
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start / stop failure

OPTIONAL EQUIPMENTS

- Charge ampmeter
- Circuit breakers (In automatic models)
- Residential / Critical type silencer
- Sound-proof canopy or container
- Mobile trailer and truck installation
- Synchronization panel for 2-32 gensets
- 3 pole / 4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Anticondensation heater
- Fuel automation systems
- Different IP and Insulation class alternator
- PMG

INTERNATIONAL QUALITY STANDARD

- EN12601, EN60204, EN12100, EN61000, EN55011
- TS ISO 8528, TS ISO 3744, TS ISO 3746, TS ISO 13857
- EN60034, EN55014, ISO 3046, BS5000, IEC 60034
- VDE 0530, BSE 4999, EN60335, IEC 60335-1:2004



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender

MODEL				N BD XX 0385	N BD XX 0440	N BD XX 0500
GROUP	GEN-SET POWER	STAND BY	kVA	385	440	500
			kW	308	352	400
		PRIME	kVA	350	400	455
			kW	280	320	364
	CANOPY DIMENSION (W x L x H) mm			1400 x 3705 x 2645	1400 x 3705 x 2645	1600 x 4400 x 2650
	CANOPY WEIGHT kg			2860	2950	4105
	OPEN DIMENSION (W x L x H) mm			1400 x 3250 x 1750	1400 x 3250 x 1750	1600 x 4000 x 2220
	OPEN WEIGHT			2455	2550	3590
ENGINE	BRAND			BAUDOUIN	BAUDOUIN	BAUDOUIN
	TYPE			6M21G385/5e2	6M21G440/5e2	6M21G500/5
	POWER	STAND BY	kW	385	405	450
		PRIME	kW	350	368	409
	SPEED (rpm)			1500	1500	1500
	CYCLE			4	4	4
	DISPLACEMENT (lt)			12,54	12,54	12,54
	NUMBER OF CYLINDERS			6 CYLINDERS INLINE	6 CYLINDERS INLINE	6 CYLINDERS INLINE
	BORE x STROKE (mm x mm)			127 X 165	127 X 165	127 X 165
	COMPRESSION RATIO			16:1	16:1	16,5:1
	GOVERNOR TYPE			ELECTRONIC		
	INDUCTION			TURBOCHARGED - INTERCOOLER		
	COMBUSTION SYSTEM			DIRECT		
	COOLING SYSTEM			WATER		
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		82,1	85,0	112,9
		%75 PRIME POWER		60,6	63,5	77,8
		%50 PRIME POWER		40,9	43,1	52,0
	TOTAL LUBRICATION SYSTEM CAPACITY (lt)			36	36	36
	TOTAL COOLANT CAPACITY (lt)			65	65	69,2
	FUEL TANK CAPACITY (lt)			890	890	1145

Npower reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice. All rights reserved.

