

165 kVA - 290 kVA

ENGINE

- G-Drive Series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged / turbocharged & air to air charge cooled
- Direct injection
- Mechanic / electronic governor system
- 12 / 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine jacket water heater (In automatic models)
- Maintenance and operating instructions

ALTERNATOR

- Brushless, single bearing
- H Class insulation type
- IP21-23 Protection class
- Self exciter
- Automatic voltage regulator
- 2/3 Pitch factor windings
- 4 Poles

AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

QUALITY STANDARD DIRECTIVES

- 2006/42/EC (Machinery Directive)
- 2014/30/EC (EMC Directive)
- 2014/35/EC (Low Voltage Directive)
- 2000/14/EC (Noise Emission Directive)

CANOPY / CONTAINER

- Modular type sound-proof canopy / container
- Easy installation type without welding canopy
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start / stop failure

OPTIONAL EQUIPMENTS

- Charge ampmeter
- Circuit breakers (In automatic models)
- Residential / Critical type silencer
- Sound-proof canopy or container
- Mobile trailer and truck installation
- Synchronization panel for 2-32 gensets
- 3 pole / 4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Anticondensation heater
- Fuel automation systems
- Different IP and Insulation class alternator
- PMG

INTERNATIONAL QUALITY STANDARD

- EN12601, EN60204, EN12100, EN61000, EN55011
- TS ISO 8528, TS ISO 3744, TS ISO 3746, TS ISO 13857
- EN60034, EN55014, ISO 3046, BS5000, IEC 60034
- VDE 0530, BSE 4999, EN60335, IEC 60335-1:2004



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender

MODEL				N DZ XX 0165	N DZ XX 0275	N DZ XX 0290
GROUP	GEN-SET POWER	STAND BY	kVA	165	275	290
			kW	132	220	232
		PRIME	kVA	150	250	264
			kW	120	200	211
	CANOPY DIMENSION (W x L x H) mm			1050 x 3580 x 1870	1400 x 3300 x 2585	1400 x 3300 x 2585
	CANOPY WEIGHT kg			1760	2480	2480
	OPEN DIMENSION (W x L x H) mm			1050 x 3100 x 1690	1400 x 3000 x 2270	1400 x 3000 x 2270
	OPEN WEIGHT			1500	2095	2095
ENGINE	BRAND			DEUTZ	DEUTZ	DEUTZ
	TYPE			WP6D152E200	BF6M1015-LA-GA	BF6M1015C-LA-G1A
	POWER	STAND BY	kW	152	231	250
		PRIME	kW	138	208	228
	SPEED (rpm)			1500	1500	1500
	CYCLE			4	4	4
	DISPLACEMENT (lt)			6,75	11,906	11,906
	NUMBER OF CYLNDERS			6 IN LINE	6 CYLINDERS- V TYPE	6 CYLINDERS- V TYPE
	BORE x STROKE (mm x mm)			105 x 130	132 x 145	132 x 145
	COMPRESSION RATIO			18:1	16.5:1	16.5:1
	GOVERNOR TYPE			ELECTRONIC		
	INDUCTION			TURBOCHARGED - AIR TO AIR CHARGE COOLED	TURBOCHARGED	TURBOCHARGED - AIR TO AIR CHARGE COOLED
	COMBUSTION SYSTEM			DIRECT INJECTION		
	COOLING SYSTEM			WATER		
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		32,64	48,53	53,20
		%75 PRIME POWER		24,56	36,4	39,90
		%50 PRIME POWER		16,65	24,26	26,60
	TOTAL LUBRICATION SYSTEM CAPACITY (lt)			16	38	38
	TOTAL COOLANT CAPACITY (lt)			28	62	62
	FUEL TANK CAPACITY (lt)			280	565	565

Npower reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice. All rights reserved.

