

66 kVA - 83 kVA

ENGINE

- G-Drive Series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged / turbocharged & air to air charge cooled
- Direct injection
- Mechanic / electronic governor system
- 12 / 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine jacket water heater (In automatic models)
- Maintenance and operating instructions

ALTERNATOR

- Brushless, single bearing
- H Class insulation type
- IP21-23 Protection class
- Self exciter
- Automatic voltage regulator
- 2/3 Pitch factor windings
- 4 Poles

AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

QUALITY STANDARD DIRECTIVES

- 2006/42/EC (Machinery Directive)
- 2014/30/EC (EMC Directive)
- 2014/35/EC (Low Voltage Directive)
- 2000/14/EC (Noise Emission Directive)

CANOPY / CONTAINER

- Modular type sound-proof canopy / container
- Easy installation type without welding canopy
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start / stop failure

OPTIONAL EQUIPMENTS

- Charge ampmeter
- Circuit breakers (In automatic models)
- Residential / Critical type silencer
- Sound-proof canopy or container
- Mobile trailer and truck installation
- Synchronization panel for 2-32 gensets
- 3 pole / 4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Anticondensation heater
- Fuel automation systems
- Different IP and Insulation class alternator
- PMG

INTERNATIONAL QUALITY STANDARD

- EN12601, EN60204, EN12100, EN61000, EN55011
- TS ISO 8528, TS ISO 3744, TS ISO 3746, TS ISO 13857
- EN60034, EN55014, ISO 3046, BS5000, IEC 60034
- VDE 0530, BSE 4999, EN60335, IEC 2015:EC8 2004



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender

MODEL				N OP XX 0066	N OP XX 0073	N OP XX 0083
GROUP	GEN-SET POWER	STAND BY	kVA	66	73	83
			kW	48,0	52,8	56,0
		PRIME	kVA	54,0	60,0	65,0
			kW	43,2	48,0	52,0
	CANOPY DIMENSION (W x L x H) mm			900x2300x1800	900x2500x1800	900x2500x1800
	CANOPY WEIGHT kg			1015	1080	1180
	OPEN DIMENSION (W x L x H) mm			900x2200x1650	900x2200x1650	900x2250x1750
	OPEN WEIGHT			910	880	980
ENGINE	BRAND			OPTIMUS	OPTIMUS	OPTIMUS
	TYPE			OPE 4.3 TWE-A	OPE 4.3 TWE-B	OPE 4.3 TWE-1
	POWER	STAND BY	kW	N/A	N/A	N/A
		PRIME	kW	N/A	N/A	N/A
	SPEED (rpm)			1500	1500	1500
	CYCLE			4	4	4
	DISPLACEMENT (lt)			3,98	3,98	4,33
	NUMBER OF CYLNDERS			4	4	4
	BORE x STROKE (mm x mm)			105/115	105/115	105/125
	COMPRESSION RATIO			17:1	17:1	17:1
	GOVERNOR TYPE			ELECTRONIC		
	INDUCTION			TURBOCHARGED		
	COMBUSTION SYSTEM			DIRECT INJECTION		
	COOLING SYSTEM			WATER		
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		14	16	19
		%75 PRIME POWER		10	11,2	14,5
		%50 PRIME POWER		7,4	7,5	9
	TOTAL LUBRICATION SYSTEM CAPACITY (lt)			13	13	13
	TOTAL COOLANT CAPACITY (lt)			17	17	20
	FUEL TANK CAPACITY (lt)			126,4	136	136

Npower reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice. All rights reserved.

