

110 kVA - 165 kVA

ENGINE

- G-Drive Series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged / turbocharged & air to air charge cooled
- Direct injection
- Mechanic / electronic governor system
- 12 / 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine jacket water heater (In automatic models)
- Maintenance and operating instructions

ALTERNATOR

- Brushless, single bearing
- H Class insulation type
- IP21-23 Protection class
- Self exciter
- Automatic voltage regulator
- 2/3 Pitch factor windings
- 4 Poles

AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

QUALITY STANDARD DIRECTIVES

- 2006/42/EC (Machinery Directive)
- 2014/30/EC (EMC Directive)
- 2014/35/EC (Low Voltage Directive)
- 2000/14/EC (Noise Emission Directive)

CANOPY / CONTAINER

- Modular type sound-proof canopy / container
- Easy installation type without welding canopy
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start / stop failure

OPTIONAL EQUIPMENTS

- Charge ampmeter
- Circuit breakers (In automatic models)
- Residential / Critical type silencer
- Sound-proof canopy or container
- Mobile trailer and truck installation
- Synchronization panel for 2-32 gensets
- 3 pole / 4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Anticondensation heater
- Fuel automation systems
- Different IP and Insulation class alternator
- PMG

INTERNATIONAL QUALITY STANDARD

- EN12601, EN60204, EN12100, EN61000, EN55011
- TS ISO 8528, TS ISO 3744, TS ISO 3746, TS ISO 13857
- EN60034, EN55014, ISO 3046, BS5000, IEC 60034
- VDE 0530, BSE 4999, EN60335, IEC 60335-1:2004



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender

MODEL				N RC XX 00110	N RC XX 00120	N RC XX 00165
GROUP	GEN-SET POWER	STAND BY	kVA	110	120	165
			kW	88	96	132
		PRIME	kVA	100	110	150
			kW	80	88	120
	CANOPY DIMENSION (W x L x H) mm			3200 x 1300 x 1800	3650 x 1300 x 1800	3650 x 1300 x 1800
	CANOPY WEIGHT kg			1980	2350	2900
	OPEN DIMENSION (W x L x H) mm			2650 x 1100 x 1800	2650 x 1100 x 1600	2800 x 1100 x 1800
	OPEN WEIGHT			1580	1750	2300
ENGINE	BRAND			RICARDO	RICARDO	RICARDO
	TYPE			R6105AZLD	R6105AZLD	R6105IZLD
	POWER	STAND BY	kW	N/A	N/A	N/A
		PRIME	kW	N/A	N/A	N/A
	SPEED (rpm)			1500	1500	1500
	CYCLE			4	4	4
	DISPLACEMENT (lt)			6,7	6,7	7,697
	NUMBER OF CYLNDERS			4 IN LINE	4 IN LINE	4 IN LINE
	BORE x STROKE (mm x mm)			105 x 130	105 x 130	110 x 135
	COMPRESSION RATIO			16:1	16:1	16:1
	GOVERNOR TYPE			ELECTRONIC		
	INDUCTION			NATURAL	TURBOCHARGED	
	COMBUSTION SYSTEM			DIRECT INJECTION		
	COOLING SYSTEM			WATER		
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		24	32	32,5
		%75 PRIME POWER		18,5	24	24,7
		%50 PRIME POWER		12	15	15,9
	TOTAL LUBRICATION SYSTEM CAPACITY (lt)			15	15	15
	TOTAL COOLANT CAPACITY (lt)			25	25	25
	FUEL TANK CAPACITY (lt)			184,8	184,8	184,8

Npower reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice. All rights reserved.

