

## 325 kVA - 440 kVA

### ENGINE

- G-Drive Series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged / turbocharged & air to air charge cooled
- Direct injection
- Mechanic / electronic governor system
- 12 / 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine jacket water heater (In automatic models)
- Maintenance and operating instructions

### ALTERNATOR

- Brushless, single bearing
- H Class insulation type
- IP21-23 Protection class
- Self exciter
- Automatic voltage regulator
- 2/3 Pitch factor windings
- 4 Poles

### AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

### QUALITY STANDARD DIRECTIVES

- 2006/42/EC (Machinery Directive)
- 2014/30/EC (EMC Directive)
- 2014/35/EC (Low Voltage Directive)
- 2000/14/EC (Noise Emission Directive)

### CANOPY / CONTAINER

- Modular type sound-proof canopy / container
- Easy installation type without welding canopy
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

### PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start / stop failure

### OPTIONAL EQUIPMENTS

- Charge ampmeter
- Circuit breakers (In automatic models)
- Residential / Critical type silencer
- Sound-proof canopy or container
- Mobile trailer and truck installation
- Synchronization panel for 2-32 gensets
- 3 pole / 4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Anticondensation heater
- Fuel automation systems
- Different IP and Insulation class alternator
- PMG

### INTERNATIONAL QUALITY STANDARD

- EN12601, EN60204, EN12100, EN61000, EN55011
- TS ISO 8528, TS ISO 3744, TS ISO 3746, TS ISO 13857
- EN60034, EN55014, ISO 3046, BS5000, IEC 60034
- VDE 0530, BSE 4999, EN60335, IEC 60335-1:2004



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender

MODEL				N RC XX 00325	N RC XX 00412	N RC XX 00440
GROUP	GEN-SET POWER	STAND BY	kVA	325	412	440
			kW	260	330	352
		PRIME	kVA	300	375	400
			kW	240	300	320
	CANOPY DIMENSION (W x L x H) mm			5000 x 1800 x 1200	5000 x 1800 x 1200	5000 x 1800 x 1200
	CANOPY WEIGHT kg			4770	5430	1150
	OPEN DIMENSION (W x L x H) mm			3800 x 1400 x 2000	3800 x 1400 x 2000	3800 x 1400 x 1200
	OPEN WEIGHT			3620	4280	4360
ENGINE	BRAND			RICARDO	RICARDO	RICARDO
	TYPE			YXR11D	YXR11D-1	WT13A-390D
	POWER	STAND BY	kW	N/A	N/A	N/A
		PRIME	kW	N/A	N/A	N/A
	SPEED (rpm)			1500	1500	1500
	CYCLE			4	4	4
	DISPLACEMENT (lt)			11,596	11,596	11,596
	NUMBER OF CYLNDERS			4 IN LINE	4 IN LINE	4 IN LINE
	BORE x STROKE (mm x mm)			126 x 155	126 x 155	126 x 155
	COMPRESSION RATIO			16:1	16:1	16:1
	GOVERNOR TYPE			ELECTRONIC		
	INDUCTION			NATURAL	TURBOCHARGED	
	COMBUSTION SYSTEM			DIRECT INJECTION		
	COOLING SYSTEM			WATER		
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		49,23	62	89
		%75 PRIME POWER		37,4	51	66
		%50 PRIME POWER		29,8	35	44
	TOTAL LUBRICATION SYSTEM CAPACITY (lt)			20	20	33
	TOTAL COOLANT CAPACITY (lt)			50	50	46
	FUEL TANK CAPACITY (lt)			240	240	240

Npower reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice. All rights reserved.

