

880 kVA - 1100 kVA

ENGINE

- G-Drive Series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged / turbocharged & air to air charge cooled
- Direct injection
- Mechanic / electronic governor system
- 12 / 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine jacket water heater (In automatic models)
- Maintenance and operating instructions

ALTERNATOR

- Brushless, single bearing
- H Class insulation type
- IP21-23 Protection class
- Self exciter
- Automatic voltage regulator
- 2/3 Pitch factor windings
- 4 Poles

AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

QUALITY STANDARD DIRECTIVES

- 2006/42/EC (Machinery Directive)
- 2014/30/EC (EMC Directive)
- 2014/35/EC (Low Voltage Directive)
- 2000/14/EC (Noise Emission Directive)

CANOPY / CONTAINER

- Modular type sound-proof canopy / container
- Easy installation type without welding canopy
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start / stop failure

OPTIONAL EQUIPMENTS

- Charge ampmeter
- Circuit breakers (In automatic models)
- Residential / Critical type silencer
- Sound-proof canopy or container
- Mobile trailer and truck installation
- Synchronization panel for 2-32 gensets
- 3 pole / 4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Anticondensation heater
- Fuel automation systems
- Different IP and Insulation class alternator
- PMG

INTERNATIONAL QUALITY STANDARD

- EN12601, EN60204, EN12100, EN61000, EN55011
- TS ISO 8528, TS ISO 3744, TS ISO 3746, TS ISO 13857
- EN60034, EN55014, ISO 3046, BS5000, IEC 60034
- VDE 0530, BSE 4999, EN60335, IEC 60335-1:2004



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender

MODEL				N RC XX 00880	N RC XX 001000	N RC XX 001100
GROUP	GEN-SET POWER	STAND BY	kVA	880	1000	1100
			kW	660	800	880
		PRIME	kVA	800	900	1000
			kW	640	720	800
	CANOPY DIMENSION (W x L x H) mm			5600 x 2100 x 2250	5600 x 2100 x 2250	5600 x 2100 x 2250
	CANOPY WEIGHT kg			10250	10300	10460
	OPEN DIMENSION (W x L x H) mm			4800 x 1900 x 2000	4800 x 1900 x 2000	5000 x 1900 x 2000
	OPEN WEIGHT			7750	7800	7960
ENGINE	BRAND			RICARDO	RICARDO	RICARDO
	TYPE			6M33D633E200	6M33D670E200	12M26D748E200
	POWER	STAND BY	kW	N/A	N/A	N/A
		PRIME	kW	N/A	N/A	N/A
	SPEED (rpm)			1500	1500	1500
	CYCLE			4	4	4
	DISPLACEMENT (lt)			31,4	31,15	31,15
	NUMBER OF CYLNDERS			4 IN LINE	4 IN LINE	4 IN LINE
	BORE x STROKE (mm x mm)			140 x 170	138 x 168	138 x 168
	COMPRESSION RATIO			17:1	16:1	16:1
	GOVERNOR TYPE			ELECTRONIC		
	INDUCTION			NATURAL	TURBOCHARGED	
	COMBUSTION SYSTEM			DIRECT INJECTION		
	COOLING SYSTEM			WATER		
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		150	150	216
		%75 PRIME POWER		120	121	165
		%50 PRIME POWER		80	80	123
	TOTAL LUBRICATION SYSTEM CAPACITY (lt)			60	60	60
	TOTAL COOLANT CAPACITY (lt)			130	130	130
	FUEL TANK CAPACITY (lt)			1100	1100	1100

Npower reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice. All rights reserved.

