

550 kVA - 715 kVA

ENGINE

- G-Drive Series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged / turbocharged & air to air charge cooled
- Direct injection
- Mechanic / electronic governor system
- 12 / 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine jacket water heater (In automatic models)
- Maintenance and operating instructions

ALTERNATOR

- Brushless, single bearing
- H Class insulation type
- IP21-23 Protection class
- Self exciter
- Automatic voltage regulator
- 2/3 Pitch factor windings
- 4 Poles

AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

QUALITY STANDARD DIRECTIVES

- 2006/42/EC (Machinery Directive)
- 2014/30/EC (EMC Directive)
- 2014/35/EC (Low Voltage Directive)
- 2000/14/EC (Noise Emission Directive)

CANOPY / CONTAINER

- Modular type sound-proof canopy / container
- Easy installation type without welding canopy
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start / stop failure

OPTIONAL EQUIPMENTS

- Charge ampmeter
- Circuit breakers (In automatic models)
- Residential / Critical type silencer
- Sound-proof canopy or container
- Mobile trailer and truck installation
- Synchronization panel for 2-32 gensets
- 3 pole / 4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Anticondensation heater
- Fuel automation systems
- Different IP and Insulation class alternator
- PMG

INTERNATIONAL QUALITY STANDARD

- EN12601, EN60204, EN12100, EN61000, EN55011
- TS ISO 8528, TS ISO 3744, TS ISO 3746, TS ISO 13857
- EN60034, EN55014, ISO 3046, BS5000, IEC 60034
- VDE 0530, BSE 4999, EN60335, IEC 2015:EC8 2004



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender

MODEL				N BD XX 0550	N BD XX 0660	N BD XX 0715	
GROUP	GEN-SET POWER	STAND BY	kVA	550	660	715	
			kW	440	528	572	
		PRIME	kVA	500	600	650	
			kW	400	480	520	
	CANOPY DIMENSION (W x L x H) mm				1600 x 4400 x 2650	1800 x 4500 x 3075	1800 x 4500 x 3075
	CANOPY WEIGHT kg				4150	5590	5590
	OPEN DIMENSION (W x L x H) mm				1600 x 4000 x 2220	1800 x 4290 x 2340	1800 x 4290 x 2340
	OPEN WEIGHT				3630	4900	4900
ENGINE	BRAND			BAUDOUIIN			
	TYPE			6M26G550/5e2			
	POWER	STAND BY	kW	484	572	633	
		PRIME	kW	440	520	575	
	SPEED (rpm)			1500			
	CYCLE			4			
	DISPLACEMENT (lt)			15,90			
	NUMBER OF CYLNDERS			6 CYLINDERS INLINE			
	BORE x STROKE (mm x mm)			150 X 150			
	COMPRESSION RATIO			15,7:1			
	GOVERNOR TYPE			ELECTRONIC			
	INDUCTION			TURBOCHARGED - INTERCOOLER			
	COMBUSTION SYSTEM			DIRECT			
	COOLING SYSTEM			WATER			
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		104,9	122,8	134,7	
		%75 PRIME POWER		78,4	92,8	90,3	
		%50 PRIME POWER		53,6	64,4	76,8	
TOTAL LUBRICATION SYSTEM CAPACITY (lt)			50	60,5	60,5		
TOTAL COOLANT CAPACITY (lt)			142	126,63	126,63		
FUEL TANK CAPACITY (lt)			1145	1530	1530		

Npower reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice. All rights reserved.

